

# INTUITIVE AND INFORMATIVE

## WIRELESS CONTROL SET

- Bluetooth® with controller screen
- Relevant operational information is displayed through images
- Engine performance indicators SAE (J1939) codes display



## Removable RAM® control system



## Interchangeable Controls-Blower with exclusive RFID key system




## Unit inclination indicator



## Impeller casing position



## Joystick functions visualization



## Engine performance indicators and DTCs

VOHL inc. reserves the right to change any specifications without prior notice.

## OTHER PRODUCTS AVAILABLE

- Ribbon snow blower
- Wood chipper\*
- Generator\*
- Water pump\*
- Brush cutter\*



368 St-Gilbert  
St-Marc-des-Carières (Quebec)  
Canada GOA 4B0

Phone : 418 268-3527  
Toll free : 1 877 901-3527  
Fax : 418 268-5640  
vohl@vohl.ca



# VL-275 VL-350

## DETACHABLE SNOW BLOWER

Dual Augers Model



vohl.ca

# FLEXIBILITY


## Dual augers model

The Vohl dual-screw conveyor is the essential tool for any snow removal fleet, known for its unmatched durability. Like a Swiss army knife, it adapts seamlessly to all conditions, whether dealing with hardened, icy, or piled snow. Its exceptional versatility ensures an efficient and reliable response to all your snow removal needs.

## Ribbon model

The Vohl ribbon conveyor, with a deeper inlet compared to the screw conveyor will primarily be utilized for collecting large quantities of fresh snow, particularly in airport environments or areas where snow has already been processed and piled, ready for truck loading, mainly in urban settings.

### Engine Module



## DIMENSIONS

Varies with options

<b>Overall height :</b>	3353 mm (132 in)
<b>Overall width :</b>	2794-2908 mm (110-114,5 in)
<b>Overall length :</b>	2438-2489 mm (96-98,5 in)
<b>Working height :</b>	1448 mm (57 in)
<b>Weight VL-275 :</b>	4717 kg (10400 lbs)
<b>Weight VL-350 :</b>	4962 kg (10940 lbs)

\* (varies depending on selected options)

## PERFORMANCE

Depending on snow conditions

<b>Capacity:</b>	Up to 3500 tons / hour
<b>Casting distance :</b>	Up to 46 m (150 ft) Through the impeller casing

\*Available from 2026.

# VL-275 / VL-350

# ROBUSTNESS AND DURABILITY



## ENGINE

- VL-275 :** 231-243 kW (310-326 hp) Stage V / Tier IV Final
- VL-350 :** 254-272 kW (340-365 hp) Stage V / Tier IV Final

## POWER TRAIN SYSTEM

- Self-adjusting clutch electric hydraulic type
- Fully enclosed oil bath
- Chain and gear type reduction protected by two (2) sets of shear bolts

## HYDRAULIC SYSTEM

- Hydraulic pump directly mounted to engine auxiliary drive
- Hydraulic-electric valve type

## AUGER

- 2 phases type with 2 augers **1**

## TRUCK LOADING CHUTE

- Made from chromium carbide
- Hydraulically controlled
- Manual tilt for easier transportation
- Horizontal rotation 300° (total)
- Projection distance between 0,9 and 15,2 m (3 to 50 ft)

## IMPELLER CASING

- Hydraulically rotating chromium carbide impeller
- Diameter 1016 mm (40 in)
- Projection distance : Until 45,7 meters (150 ft)

## IMPELLER

- Diameter de 990 mm (39 in)
- Five (5) bolt-on type and concave impeller blades

## OPTIONS

- Anti-slip steps and grab handles
- Loader Z-bar protection
- Electronic inclinometer
- Chromium carbide impeller
- Hydraulically-electrically controlled chute tilt **2**
- Extendable loading chute from 3353 to 4039 mm **3** (132 to 159 in) from ground
- Female quick coupler
- Wireless, remote shutdown system for flagman
- Removable control box for maintenance
- Working light options for the engine and electrical compartments and the front and rear shear bolts

Superior quality, exceptional performance

# VOHL